# TECHNOMAC SNC

Industrial Machinery & Spare Parts

**Document generated:**
November 28, 2026

**Reference:**
TECH2026043b87

## SAKURAI Oliver 272 - 2003 - SN: GE 122 303

**Brand:** SAKURAI | **Category:** Offset Printing Presses | **Ref:** TECH2026043b87

**AVAILABLE**












### MACHINE SPECIFICATION

| | |
|---|---|
| **Reference Code** | **TECH2026043b87** |
| **Brand** | **SAKURAI** |
| **Category** | **Offset Printing Presses** |
| **Condition** | **Used** |
| **Status** | **Available** |

### TECHNICAL DATA

| | |
|---|---|
| **Max Sheet Size** | **72 x 52 cm (28 x 20 inch)** |
| **Max Speed** | **12000 sheets / hour** |
| **Colors** | **2 Colors** |
| **Dimensions** | **3.90 m x 2.30 m x 1.95 m** |
| **Weight** | **6300.00 kg** |

### DESCRIPTION

Configuration: 2-color sheet-fed offset press.

Year: Manufactured until 2003.

Impressions: Typically ranges from 15 mio to 60 mio depending on the specific unit's history.

Max paper size: 52 x 72 cm (20.5 x 28.3 inches).

Max printing size: 50.8 x 71 cm.

Dampening system: Olivermatic continuous alcohol dampening system, often paired with Technotrans cooling and recirculation.

Plate changing: S-APC (Semi-Automatic Plate Changer).

Max speed: 12,000 sheets / hour.

Inking control: SCC (Sakurai Colour Console) for remote ink and register control.

Washing devices: Automatic ink roller and blanket wash-up devices.

Powder spray system: Integrated powder sprayer (typically Grafix or similar digital units).

Delivery capacity: High pile delivery.

Substrate thickness: 0.04 mm to 0.6 mm.

Registration: SAS (Sakurai Auto Set) touch screen console for automatic size and thickness presets, plus electronic double sheet detection.

PRICE

## Available on Request

### INTERESTED IN THIS MACHINE?

Contact us for pricing, detailed specifications, or to schedule a viewing.

**Request a Quote:**

https://api.technomac-snc.com//machines/019db026-87ee-725d-bca1-2f94b236bc53

**Email:** info@technomac-snc.com

**Website:** www.technomac-snc.com



This document was automatically generated. All specifications are subject to verification.